



YELLOW DISCO

Warranty 10 YEARS

Application temperature FROM +15°C TO +25°C

Storage from +5°C to +35°C **3 YEARS**

LENGTH 30 m

WIDTH ←→ 122 cm

CHARACTERISTICS

Primer/Primer +	~
Kraft paper release	~
liner	
Stretchable	×
PET	~
Interior installation	~
Outside installation	×
UV-Resistant	×
Permanent adhesive	~
Appearance	Glitter
Thickness	$400~\mu$
Scratch-proof	Average

CERTIFICATIONS

CE	~
IMO	×
MED	×
RAIL	~
REACH	~
TCHIBO	~
TABER TEST	~
VOC	~

GENERAL

ADHESIVE STRENGTH:

91 minutes after installation 1.04 Kg/cm 24 hours after installation: 1.43 Kg/cm 3 days after installation: 1.51 Kg/cm 7 days after installation: 1.65kg/cm

ADHESIVE STRENGTH AT HIGH TEMPERATURE:

After the 1st day: 1.37 Kg/cm After 7 days: 1.03 Kg/cm

DURABILITY:

This product offers exceptional resistance to water, dirt, abrasion, UV rays and wear (yellowing, crackling, scaling, delamination).

MAINTENANCE:

For daily care and maintenance of the film use only neutral pH detergents, do not use products with too much acidic or basic pH.

- much acidic or basic pH.

 Hot water (not boiling) can help eliminate stubborn stains
 In some cases, even a solution based on isopropyl alcohol and water can be effective (70% ISO 30% H2O. Not on printed Cover Styl')

 Use only soft cloths or sponges to clean the vinyl (except glitter)
 If persistent stains are present it means that care and maintenance have not been performed correctly. In this case carry out a repair with patch (not guaranteed but effective and economical) or complete replacement of the vinyl;
- Don't use any organic-based cleaning product like ammonia or polish to clean vinyl